Converting Alternative Fuel Units to Gasoline Gallon Equivalents (GGE)

Every fuel has different energy density. The most common way to measure how much petroleum is displaced through the use an alternative fuel is to convert the energy density of an alternative fuel unit to the energy density in a gasoline gallon.

The table below lists the GGE calculation for each alternative fuel. To perform a conversion, choose the GGE calculation for the appropriate fuel type. Next, drop the number of fuel units used into the equation, and multiply that number by the proper conversion factor.

Example

If you used 115 gallons of B20, the equation would be: 115 gal B20 x 1.126 = 129.49 GGE

Alternative Fuel Conversion Factors to GGE			
Fuel Type	Fuel Measurement Unit	Conversion Factor	GGE Calculation
B100	gallons	1.015	GGE = B100 gal x 1.015
B20	gallons	1.126	GGE = B20 gal x 1.126
CNG	gallons at 2400 psi	0.18	GGE = CNG gal (at 2400 psi) x 0.18
CNG	gallons at 3600 psi	0.27	GGE = CNG gal (at 3600 psi) x 0.27
CNG	gallons at 3000 psi	0.225	GGE = CNG gal (at 3000 psi) x 0.225
CNG	hundred cubic feet	0.83	GGE = CNG ccf x 0.83
Diesel	gallons	1.147	GGE = Diesel gal x 1.147
E-85	gallons	0.72	GGE = E-85 gal x 0.72
Electric	kWh	0.03	GGE = Ele kWh x 0.03
Gasoline	gallons	No conversion needed	GGE = Gasoline gal
Hydrogen	kg	1	GGE = H2 kg x 1
LNG	gallons @ 14.7psi and -234 degrees F	0.66	GGE = LNG gal x 0.66
LPG	gallons	0.74	GGE = LPG gal x 0.74